

TECHNICAL SPECIFICATIONS, TECHNICAL GASES TAPS

Use of perforated copper bar according to EN 12168 norm and solid cooper bar according to EN 12164 norm, stamping material on solid bar EN 12165.

The taps for technical gases are supplied with fine regulation head-valve with PTFE seal.

Fixed nozzle according to DIN 12898 norm.

Handles produced in polypropylene, antacid material. Colouring of the handles according to EN 13792 norm.

Threading according to ISO 228/1 norm, class of tolerance B.

Taps fabricated according to DIN 12918 norm.

Maximum pressure of use 7 bar.

The taps for oxygen are supplied with lubricated head-valves with specific grease.

TECHNICAL GASES TAPS

| Important: indicate <u>always</u> gas/fluid example: CO 3001 vacuum or CO3060 compressed air | | |
|---|---|--|
| Standard supply | Options without change on price | Options with change on price |
| Fixed nozzle | Removable nozzle Rifer to our article S example: CO3004S | |
| Head-valve with fine regulation with PTFE seal | | Head-valve for oxygen Rifer to our article VO example: CO3010VO |
| Offspring 3/8" 30 mm. wall mounted taps and 80 mm. Bench-mounted taps | Offspring 1/2" 30 mm. Wall mounted taps and 80 mm. Bench-mounted taps Rifer to our article 1/2" example: CO3011 1/2" | |
| | | As per other particular exigencies, we can also include other modifications, such as: height or centre to centre, etc. Evaluated under specific request |