

TECHNICAL SPECIFICATIONS, EMERGENCY SHOWERS AND EYE WASHES

Models IO.....SS with stainless steel bowl and/or head shower.



EMERGENCY SHOWERS AND EYE WASHES

Standard supply			
EYE WASH		SHOWER	
Bowl material	Polypropylene - Stainless steel	Bowl material	Polypropylene - Stainless steel
Connections	Brass	Connections	Brass
Nozzle	Aerate	Piping	Zincd steel
Total max flow rate	14 l/min \pm 10% (a 0,3 MPa)	Head shower material	Polypropylene - Stainless steel
Entrance	1/2" F	Flow rate:	
Outlet	1,1/4" F	Eye washes	14 l/min \pm 10%
Activation	with lateral push	Showers	More than 120 l/min. a 0,3 MPa
Recommended water temperature	min. 15° -max35° C	Finishing	Epoxy painting
Entrance pressure	min. 0,2 MPa - máx. 0,5 MPa	Entrance pressure	min. 0,2 MPa - máx. 0,5 MPa
Minimum required flow rate	6 l/min. a 0,2 MPa	Minimum required flow rate	100 l/min a 0,2 MPa
Color	Green - RAL 6029	Color	Green - RAL 6029

IN COMPLIANCE WITH:

UNI 9608

UNI 10271

DIN 12899 PART. 2

ANSI Z 358.1 - 2004

DIRETTIVA EUROPEA 93/42/CEE

(medical device)

prEN15154-1