

IO – EMERGENCY SHOWERS AND EYE WASHES

SHOWERS		EYEWASH	
Shower head material	polypropylene/stainless steel	Bowl material	polypropylene/stainless steel
Connection	brass	Double arms	chromed brass
Tubes	galvanized steel	Aerator protection cup	EPDM
Flow	aerated	Eyewash cover	plastic
Water flow (max)	120 l/min at 0,3 MPa	Push	steel
Required water flow	100 l/min	Tubes	galvanized steel
Recommended water temperature	min. 15°C - max 35°C	Connection	brass
Dynamic power supply pressure	min.0,2 -max 0,5 MPa	Flow	aerated
External finishing	epoxy powder coating	Water flow (max)	14 l/min
Colour	green RAL 6029	Required water flow	6 l/min
With warning sign:	 	Recommended water temperature	min. 15°C - max 35°C
		Dynamic power supply pressure	min.0,2 -max 0,5 MPa
		Colour	green RAL 6029
COMPLIANT WITH REGULATIONS: UNI 9608 UNI 10271 UNI7546/2 UNI7546/3 UNI7546/4 DIN 12899 PART. 2 ANSI Z 358.1– 2014 EN15154-2		Available versions on request: IO.... SS in stainless steel AISI 304 bowl/shower head IO.... X in stainless steel AISI 304 IO.... XX in stainless steel AISI 316	