

BO – COMBUSTIBLE GASES TAPS

Use of drilled brass bar according to EN 12168 norm and solid brass bar according to EN 12164 norm, molded material obtained from solid bar according to EN 12165 norm, copper tube according to EN12449 norm.

Combustible gases taps supplied with ceramic head-valve with safety lock.

Fixed nozzle, built according to DIN 12898.

Handles made of polypropylene, acid-resistant material.

Handles colouring according to EN 13792.

Threads according to ISO 228/1, tolerance class B.

Taps built and approved according to DIN 12918 norm.

Surface external finishing with epoxy powder coating.

Combustible gases taps are tested at medium pressure of 0,2 bar.

Standard supply		Options	Code
Fixed nozzle		Taps fabricated and approved according to DIN 12918 norm No changes available	
Ceramic head-valve with safety lock			
Threaded part 3/8" Wall mounted articles length 30 mm Bench mounted articles length 80 mm		Threaded part 1/2" different lengths on request	example: BO....1/2 to specify
Additional accessories, available in connection and fittings section			Code
Wall mounted taps (1/2") Wall mounted taps (3/8")	Flexible for gas cm.150 F1/2 – F1/2 + elbow connection 90° connection with welded copper tube		023 + 024 021
Bench mounted taps (1/2") Bench mounted taps (3/8")	Flexible for gas cm.150 F1/2 – F1/2 Straight connection with welded copper tube Swivelling cap with welded copper tube		023 020 022